

DESOI AirPower M25-2C VA

No. 17589

Description

The reciprocating pump DESOI AirPower M25-2C is equipped with a forced mixing control. The material is delivered at a fixed mixing ratio of 1 : 1. The big and exactly operating valves provide both high flow rate and high mixing accuracy. The pump is very easy to maintain and low wearing. Due to its low weight, the pump can be used flexibly on the construction site.

Material to be used

- acrylate gel

Delivery range

moving device, 1.5 m suction system Ø 20 mm with suction basket Ø 40 mm: component A: transparent, component B: black, 2 x manometer 0 – 250 bar, material hose connection: component A: external thread M16x1.5; component B: external thread M14x1.5; return hoses Ø 8 mm: transparent, air connection: air plug NW 7.2; incl. instruction manual

Advantages

- Pressure gauge units with manometers at machine outlet for pressure control of each component
- All material contacting parts of stainless steel



1. Pressure reducer with manometer and anti freeze unit

2. Pressure gauge with oil lubrication

Technical data

Working pressure – infinitely variable	15 – 220 bar
Delivery rate	
- at compressor output of 0.7 m ³ /min (2 x compressor DESOI R400)	max. 8 l/min
- at compressor output of 1.5 m ³ /min	max. 10 l/min
Air consumption	1 m ³ /min
Mixing ratio	1 : 1
Air pressure	max. 8 bar
Weight	40 kg
L x W x H	65 x 50 x 85 cm

Accessories

	No.
Spare and wear part set DESOI AirPower M25-2C	17589-EVS
Set of tools DESOI AirPower M25A-3C VA	17599-WS