

## DESOI PowerInject P1

No. 15747

### Description

The small, compact, powerful reciprocating pump DESOI PowerInject P1 is made for machine usable injection resin. As the pump is equipped with a pressure gauge unit with membrane and oil filling, the manometer cannot get stuck as there is no direct contact with the injection resin.

### Material to be used

- Epoxy resin
- Polyurethane

### Delivery range

drive, pressure control with return and pressure gauge unit with manometer 0 – 250 bar, 2 litre material container transparent, incl. instruction manual, No. 16802: HP material hose - steel (Ø 6 mm, 3 m long, union nuts M12x1.5, solvent resistant), No. 16733: HP injection gun (external thread M12x1.5, whip 0.3 m, 0 – 250 bar, mouth piece)

### Advantages

- Seals can be retightened manually - long life
- Exact adjustment of pressure
- Easy operation and cleaning



1. Pressure gauge unit with manometer and pressure regulating valve

### Technical data

Supply	230 V
Motor power	0.8 kW
Working pressure - infinitely variable	10 – 200 bar
Delivery rate	max. 0.4 l/min
Weight	8.3 kg
L x W x H	36 x 19 x 53 cm

### Accessories

	No.
Spare and wear part set DESOI PowerInject P1	15735-EVS
Set of tools DESOI PowerInject P1	15735-WS