

## DESOI M-Power 60Z

No. 10752

### Description

The handy and compact manual reciprocating pump DESOI M-Power 60Z is efficient and suitable for quick service on site. The ready-mixed material is sucked directly out of the mixing container.

### Material to be used

- Injection mortar
- Cement paste
- Cement suspension
- Aqueous solution, e. g. micro emulsion

### Delivery range

suction system, accumulator with manometer  
0 – 25 bar, incl. instruction manual,  
No. 10913: Material hose (Ø 13 mm, 3 m long,  
detachable double nipple R ½"),  
No. 10920: Quick snap (LP ball valve R ½", max.  
40 bar, free passage Ø 9 mm, detachable double  
nipple R ½"),  
No. 21232: LP ball valve R ½" (max. 40 bar, mouth  
piece, detachable double nipple R ½")

### Advantages

- Accumulator with manometer for pressure control and constant material output
- Big material passages - high flow rate
- Space-saving transport - collapsible



1. Accumulator with manometer

2. Material hose with ball valve and quick snap, ball valve with mouth piece

### Technical data

Working pressure - acc. to compressive force	0 – 20 bar
Delivery rate	150 ml/stroke
Grain size	max. 0.3 mm
Weight	20 kg
L x W x H - working position	85 x 37 x 77 cm
L x W x H - transport	80 x 37 x 41 cm

### Accessories

	No.
Spare and wear part set DESOI M-Power 60Z	10752-EVS
Set of tools DESOI M-Power 60Z	10752-WS