

## DESOI AirPower XL50-2C

No. 17565

### Description

The reciprocating pump DESOI AirPower XL50-2C achieves a delivery of max. 25 l/min at a mixing ratio of 1 : 1. Due to the big valves and pistons also highly viscous material can be used without any problems.

### Material to be used

- 2 component injection resin

### Delivery range

moving device with wheel set, suction system,  
2 x manometer 0 – 400 bar, incl. instruction manual

### Advantages

- Manometers at machine outlet for pressure control of each component
- Big material passage - suitable also for highly viscous material
- Adjustment of the material volume



1. Manometer combination

2. Pressure regulator with manometer and anti-freeze device

### Technical data

|  |                         |
|--|-------------------------|
| Working pressure - infinitely variable | 20 – 140 bar            |
| Delivery rate                          | max. 25 l/min           |
| Air consumption                        | 2.5 m <sup>3</sup> /min |
| Pressure ratio                         | 1 : 20                  |
| Mixing ratio                           | 1 : 1                   |
| Air pressure                           | max. 7 bar              |
| Weight                                 | 105 kg                  |
| L x W x H                              | 110 x 55 x 65 cm        |

### Accessories

|  | No.       |
|--|-----------|
| Spare and wear part set DESOI AirPower XL50-2C | 17565-EVS |
| Set of tools DESOI AirPower XL50-2C            | 17565-WS  |